



# FRENCH INSWING PATIO DOOR









#### PLY GEM MIRA PREMIUM SERIES WINDOWS HAVE BEEN GREEN APPROVED BY THE HOME INNOVATIONS RESEARCH LAB.

This means you can be assured that Ply Gem MIRA Premium Series windows comply with specific green practice criteria in the National Green Building Standard. Visit www.homeinnovation.com/greenproducts for more details.

#### FRENCH INSWING PATIO DOOR NFRC CERTIFIED 2.86 0.35 0.17 0.32 2.94 0.34 0.13 0.25 3.13 0.32 0.17 0.31 3.13 0.32 0.13 0 24 3 33 0.3 0.15 0.24 3.33 0.3 0.11 0.15 3 45 0.29 0.14 0.24 3 45 0.29 0.1 0.15 7/8" HP Glass 3.03 0.33 0.17 0.32 3.03 0.33 0.13 0.25 0.17 0.31 3.23 0.31 3.13 0.32 0.13 0.24 3.45 0.29 0.15 0.24 0.11 3 45 0.29 0.15 3.57 0.14 0.24 0.28 3 57 0.28 0.1 0.15

Most unit sizes **ENERGY STAR®** qualified in most zones and may be eligible for LEED for Homes\* credits.

\*LEED for Homes is a rating system of the U.S. Green
Building Council that promotes the design and construction of high-performance green homes



All units rated in accordance with NFRC 100/200 standards by a NAMI Accredited lab. Performance values reflect the performance of units tested with the following configuration: 3mm glass, no grilles and Warm Edge spacer system and Warm Edge+ spacer system.

R VALUE: Restrictive ambient air flow; U FACTOR: Rate of heat loss; SHGC: Solar Heat Gain Coefficient; VT: Visible Transmittance

1. Coastal hardware is optional

## STANDARD EXTERIOR CLADDING COLOR OPTIONS


















NOTE: Colors shown are close approximations and may not be accurate representations for color matching. Please request color swatches from your Ply Gem sales representative to do so. See MIRA product brochure or website for additional signature or radiance colors.

## STANDARD FEATURES

- Adjustable hinges are standard for smooth operation
- Locking shoot bolts at head and sill for
- Thermally broken sill for increased thermal
- Aluminum astragal with stainable wood interior
- Full-perimeter weatherstripping for air-tight performance and smooth operation
- Multi-point locking system
- 1 ¾" panels with wide stiles and rails for true
- Select clear wood interior ready for paint or stain to match any interior décor (also available in primed or prefinished in white, black and off-white)
- Durable .080 extruded aluminum cladding on exterior surfaces of panels and .050 extruded aluminum cladding on frame resists dings and dents while providing structural integrity











## **OPTIONS**

#### **GLASS OPTIONS:**

HPSC, HP2+, HP2+SC, HP2MAX, HP2MAXSC, HP3MAX, HP3<sub>MAX</sub>SC (Low-E, Low-ESC and Low-E2+ for high altitude applications), Warm Edge+, tinted, obscure, laminated and black spandrel



## **GRILLE OPTIONS:**

Color-coordinated grilles-between-the-glass (GBG) (SDL) available in  $^7/_8$ " and 1  $^1/_4$ ";  $^7/_8$ " full surround removable wood grilles



### **EXTERIOR CASING:**

J Channel, 180 Brick Mould, 3 1/2" Flat, 3 1/4" Williamsburg available as either factory or field applied

#### **EXTENSION JAMBS:**

natural "clear" wood

## **HARDWARE OPTIONS:**

Traditional handle sets available in bright brass, antique brass, oil rubbed bronze and satin nickel. handle sets available in coastal bright brass, coastal satin nickel and oil-rubbed bronze. Flat hinges optional

#### PRODUCT CONFIGURATION:

Transoms, circle heads, ellipticals, arches, side lites and various architectural shapes

